

SPECIFICATIONS


RoHS Compliant



Model Number: GLD24B3E2X-E3
Part Number: 17001171A

Rev: 00
Jun. 12 2018

Mechanical Drawing:



Motor:

Nominal Voltage	= 24V DC
Operating Voltage Range	= 16 – 32V DC
Nominal Running Current	= 0.63 Amps
Max. Locked Rotor Current	= 1.35 Amps
Running Power	= 15.1 Watts
Average Speed	= 3300 RPM
Bearings	= Ball
Air Flow	= 150 CFM
Acoustic	= 53.6 dB(A)

Construction:

Venturi:	Die Cast Aluminum, Black.
Propeller:	Plastic, Black, UL 94V-0.

Life Expectancy:

This fan is designed for continuous duty life of 60,000 hours at 70°C (L10).

Termination:

12"±1" (304.8±25.4mm)	22AWG UL1061 Leadwires
Red	= Power(+)
Black	= Return(-)
Blue/White	= Tach output
Yellow	= PWM control

Additional Features:

- Brushless DC Motor
- Solid State Circuitry
- Electronic Locked Rotor Protected
- Polarity Protection
- Automatic Restart
- Operating Temperature: -10 °C to +70 °C
- Storage Temperature: -40 °C to +85 °C
- Environmental Protection: Type 3(IP68)

TACHOMETER:

Output:	Open Collector
Ic:	20 mA max.
Vcc:	32 Vdc max.
Pulses per Revolution:	2
Isolated:	No

Speed Control:

- PWM: 200 ~ 2 KHz, Open Collector
- <10% Duty: Off
- 10%~95% Duty: Linear Ramp
- >95% Duty or Open Lead Wire: Full Speed

Agency Approvals:

UL, CUL, CE

PQ Curve:

